

# DL6MB Floor type Low Speed Refrigerated Centrifuge



## Application

It is widely used in the field of blood station, pharmaceutical factory, biochemistry, biological products and so on. It is the ideal instrument for blood separation, protein precipitation and cell collection.


## Features

1. Brush-less frequency motor drive, maintenance is free
2. Floor type low speed large capacity refrigerated centrifuge
3. Melt housing, 304# stainless steel centrifugal chamber, safe and reliable.
4. Microprocessor control and digital display run parameters like speed, RCF and time.




















## Technical Specifications

Max. RPM/RCF	Angle Rotor	6,000/6600xg	
	Swing Out Rotor	4,200/5100xg	
Max. Capacity	Angle Rotor	6x500ml	
	Swing Out	6x1000ml	
Timer	99h~59min	RPM/RCF conversion	Yes
Noise level (dB)	≤58	Acc/Dec (sec)	There are 10 rates for your choice
Digital display	Yes	Safety lid lock system	Auto electric lid lock with Alarm
Power supply	220V 60Hz	Temperature range	-20℃~40℃
Product Dimension	800x740x930mm	Package Dimension	1275x1115x1340mm
Weight (kg)	N.W:260kg	G.W:305kg (wooden box)	
Certificates	CE,ISO & Calibration report are available		

# Optional Rotors for DL6MB

Image	Rotor No.	Volume(ml)	Max. Speed (RPM)	Max. RCF (×g)
	30298	6x1000ml (Round up)	4200	5100

## NO. 40201 - 40208 Adapters for 800ml bucket

Tube Image								
Volume	37x5ml	23x7ml	14x15ml	7x50ml	5x50ml	4x70ml	3x100ml	500ml
Adapter Image								
	30221	4x300ml	6000	5390				
	30222	6x300ml	6000	5660				
	30223	6x500ml	6000	6600				